


DC KS5N-IG32




IG-32



KS5N-3545

12 [Vdc]	
5,100 [rpm]	6,000 [rpm]
240 [gf cm]	
2 [A]	400 [mA]
12.5 [W]	
70.2 [%]	
26.3 [W]	
1.7 [kgf cm]	9 [A]

KS5N-3545 DC



KS5N-3545 +

IG-32

		[rpm]	[rpm]	[kgf-cm]	[kgf-cm Max.]	[%]	L [mm]	* [g]	2017 4
KS5N-IG32-004	1/4	1,376	1,619	2.0	6.0	80	22.1	271	4,698
KS5N-IG32-005	1/5	984	1,158	2.0	6.0	80	22.1	271	4,698
KS5N-IG32-014	1/14	371	437	4.0	12.0	70	28.5	291	4,914
KS5N-IG32-019	1/19	266	312	4.0	12.0	70	28.5	291	4,914
KS5N-IG32-027	1/27	190	223	6.0	18.0	70	28.5	291	4,914
KS5N-IG32-051	1/51	100	118	8.0	24.0	60	34.9	316	5,238
KS5N-IG32-071	1/71	72	84	8.0	24.0	60	34.9	316	5,238
KS5N-IG32-100	1/100	51	60	10.0	30.0	60	34.9	316	5,238
KS5N-IG32-139	1/139	37	43	10.0	30.0	60	34.9	316	5,238
KS5N-IG32-189	1/189	27	32	12.0	36.0	50	41.3	342	5,508
KS5N-IG32-264	1/264	19	23	12.0	36.0	50	41.3	342	5,508
KS5N-IG32-516	1/516	9.9	11.6	12.0	36.0	50	41.3	342	5,508
KS5N-IG32-721	1/721	5.4	6.4	12.0	36.0	50	41.3	342	5,508

KS5N-IG32-XXX[METAL]

XXX: 004 721 KS5N-IG32-005 1/5

[METAL] (1,080)

IG-32

Web shop <http://szc.jp/shop>

<http://suzakugiken.jp/> sales@suzakugiken.jp

twitter LINE@: @suzakulab

Fax: 0742-25-5087

